


NOMINAL OUTPUT TORQUE: 40-60Nm  
 MAXIMUM OUTPUT TORQUE: 120-180Nm  
 NOMINAL INPUT SPEED: 5000RPM  
 MAXIMUM INPUT SPEED: 10000RPM  
 INERTIA:  $0.13 \sim 0.24 \text{kg} \cdot \text{cm}^2$   
 MASS: 1.3kg

SHAFT OPTION S1: SMOOTH OUTPUT SHAFT(STANDARD)  
 SHAFT OPTION S2: OUTPUT SHAFT WITH KEYWAY  
 REDUCED BACKLASH  $\leq 3 \text{arcmin}$   
 STANDARD BACKLASH  $\leq 5 \text{arcmin}$

BUSHING SUPPLIED WHEN MOTOR SHAFT DIAMETER SMALL THAN  $\varnothing 14$

PART NO. AF0601-P4020102 AF060-1, AD-W60-M60-2		 <b>APEX DYNAMICS, INC.</b>		
APPROVALS	DATE	TITLE AF060 1 STAGE, RATIO= 3-10 AND STANDARD FLANGE MOUNTING		
DRAWN Vicky	1-May-03	DWG NO. AF0601-P4020102		
CHECKED				
APPROVED Shih yi-pei	1-May-03	 SIZE A2	SCALE 1:1	REV 3.0