



NOMINAL OUTPUT TORQUE: 450-650Nm
 MAXIMUM OUTPUT TORQUE: 1350-1950Nm
 NOMINAL INPUT SPEED: 3000RPM
 MAXIMUM INPUT SPEED: 6000RPM
 INERTIA: 7.31-14.35kg-cm²
 MASS: 13.7kg

SHAFT OPTION S1: SMOOTH OUTPUT SHAFT(STANDARD)
 SHAFT OPTION S2: OUTPUT SHAFT WITH KEYWAY
 MICRO BACKLASH: 1arcmin
 REDUCED BACKLASH: 3arcmin
 STANDARD BACKLASH: 5arcmin

BUSHING SUPPLIED WHEN MOTOR SHAFT DIAMETER SMALL THAN $\phi 38$

PART NO. AF1401-P4050102 AF140-1, AD-W142-M142-2		 APEX DYNAMICS, INC.							
APPROVALS	DATE	TITLE AF140 1 STAGE, RATIO= 3~10 AND STANDARD FLANGE MOUNTING							
DRAWN		DWG NO. AF1401-P4050102							
CHECKED									
APPROVED	Shih yi-pei	1-May-03	 <table border="1"> <tr> <td>SIZE</td> <td>SCALE</td> <td>REV</td> </tr> <tr> <td>A0</td> <td>1:1</td> <td>3.0</td> </tr> </table>	SIZE	SCALE	REV	A0	1:1	3.0
SIZE	SCALE	REV							
A0	1:1	3.0							